



Modell	PC70	PC70E	PC70H	PC70F	PC70HE	PC90	PC90E	PC90H	PC90F	PC90HE
Leistung kW	6,8	6,8	6,8	6,8	6,8	9,0	9,0	9,0	9,0	9,0
Saunakabine min m <sup>3</sup>	6	6	6	6	6	8	8	8	8	8
Saunakabine max m <sup>3</sup>	10	10	10	10	8	14	14	14	14	14
Saunakabine höhe min cm	190	190	190	190	190	190	190	190	210	190
Steinkammer max kg (Steingröße Ø 5-10 cm, AC3000)	80	90	80	80	90	80	90	80	80	90
Masse/mm breite	320	320	360	360	360	320	320	360	360	360
Masse/mm höhe	930	930	930	930	930	930	930	930	930	930
Masse/mm tiefe	320	320	340	360	340	320	320	340	360	340
Gewicht kg	10	10	17	17	17	10	10	17	17	17
Netzspannung 3-Phase	400 V 3N	400 V 3N	400 V 3N	400 V 3N	400 V 3N	400 V 3N	400 V 3N	400 V 3N	400 V 3N	400 V 3N
Anschlusskabel mm <sup>2</sup>	5 x 1,5	5 x 1,5	5 x 1,5	5 x 1,5	5 x 1,5	5 x 2,5	5 x 2,5	5 x 2,5	5 x 2,5	5 X 2,5
Sicherung A	3 x 10	3 x 10	3 x 10	3 x 10	3 x 10	3 x 16	3 x 16	3 x 16	3 x 16	3 x 16
Netzspannung 1-Phase	230 V 1N	230 V 1N	230 V 1N	230 V 1N	230 V 1N	230 V 1N	230 V 1N	230 V 1N	230 V 1N	230 V 1N
Anschlusskabel mm <sup>2</sup>	3 x 6	3 x 6	3 x 6	3 x 6	3 x 6	3 x 10	3 x 10	3 x 10	3 x 10	3 x 10
Sicherung A	1 x 35	1 x 35	1 x 35	1 x 35	1 x 35	1 x 40	1 x 40	1 x 40	1 x 40	1 x 40
Steuergerät	-	Griffin, C150	-	-	Griffin, C150	-	Griffin, C150	-	-	Griffin, C150
Sicherheitsabstand/mm A	100	100	30	30	30	100	100	30	30	30
Sicherheitsabstand/mm B	100	100	100	30	100	100	100	100	30	100
Sicherheitsabstand/mm C	950	950	950	950	950	950	950	950	1150	950
Sicherheitsabstand/mm D 3N~	30	30	30	30	30	30	30	30	30	30
Sicherheitsabstand/mm D 1N~	50	50	50	50	50	50	50	50	50	50
Sicherheitsabstand/mm E	520	520	420	420	420	520	520	420	420	420
Sicherheitsabstand/mm F	520	520	470	420	470	520	520	470	420	470