

Technische Daten

Technical Data

HEIZGERÄT- MODELL	HEIZELEMENT kW TYPENUMMER			SAUNARAUM		VERSORGUNGS- SPANNUNG	HEIZGERÄTGRÖSSE			KABELSTÄRKE	STEUERUNG		SICHERUNG FUSE (AMP.)
HEATER MODEL	kW	HEATING ELEMENT TYPE	SAUNA MIN	ROOM MAX	SUPPLY VOLTAGE	BREITE	TIEFE	HÖHE	SIZE OF HEATER		STONES	CONTROL	
				(m³)		WIDTH	DEPTH	HEIGHT	(mm)		SIZE OF WIRE (mm²)	(kg)	
TH2-30NB	3.0	2 x 1.5	TH150	2	4	380-415V 2N~ 220-230V 1N~	257	257	1300	4 x 1.5/ 3 x 2.5	70	8 + 4h	2 x 10/ 1 x 16
TH3-35NB	3.5	3 x 1.15	TH115	3	6	380-415V 3N~ 220-240V 3~ 220-240V 1N~	257	257	1300	5 x 1.5/ 4 x 1.5 3 x 2.5	70	8 + 4h	3 x 10/ 3 x 10/ 1 x 20
TH3-45NB	4.5	3 x 1.5	TH150	3	6	380-415V 3N~ 220-240V 3~ 220-240V 1N~	257	257	1300	5 x 1.5/ 4 x 2.5/ 3 x 4.0	70	8 + 4h	3 x 10/ 3 x 16/ 1 x 25
TH3-60NB	6.0	3 x 2.0	TH200	5	8	380-415V 3N~ 220-240V 3~ 220-240V 1N~	257	257	1300	5 x 1.5/ 4 x 2.5/ 3 x 6.0	70	8 + 4h	3 x 10/ 3 x 20/ 1 x 32
TH2-30NS	3.0	2 x 1.5	TH150	2	4	380-415V 2N~ 220-230V 1N~	257	257	1300	4 x 1.5/ 3 x 2.5	70	separat separate	2 x 10/ 1 x 16
TH3-35NS	3.5	3 x 1.15	TH115	3	6	380-415V 3N~ 220-240V 3~ 220-240V 1N~	257	257	1300	5 x 1.5/ 4 x 1.5/ 3 x 2.5	70	separat separate	3 x 10/ 3 x 10/ 1 x 20
TH3-45NS	4.5	3 x 1.5	TH150	3	6	380-415V 3N~ 220-240V 3~ 220-240V 1N~	257	257	1300	5 x 1.5/ 4 x 2.5/ 3 x 4.0	70	separat separate	3 x 10/ 3 x 16/ 1 x 25
TH3-60NS	6.0	3 x 2.0	TH200	5	8	380-415V 3N~ 220-240V 3~ 220-240V 1N~	257	257	1300	5 x 1.5 4 x 2.5/ 3 x 6.0	70	separat separate	3 x 10/ 3 x 20/ 1 x 32
TH4-60NB	6.0	4 x1.5	TH150	5	9	380-415V 3N~ 220-240V 3~ 220-240V 1N~	310	310	1300	5 x 2.5/ 4 x 4.0/ 3 x 6.0	105	8 + 4h	3 x 16/ 3 x 25/ 1 x 32
TH4-60NS	6.0	4 x 1.5	TH150	5	9	380-415V 3N~ 220-240V 3~ 220-240V 1N~	310	310	1300	5 x 2.5/ 4 x 4.0/ 3 x 6.0	105	separat separate	3 x 16/ 3 x 25/ 1 x 32
TH4-80NS	8.0	4 x 2.0	TH200	7	13	380-415V 3N~ 220-240V 3~ 220-240V 1N~	310	310	1300	5 x 2.5/ 4 x 6.0/ 3 x 10	105	separat separate	3 x 20/ 3 x 32/ 1 x 40
TH5-90NS	9.0	2 x 1.5 3 x 2.0	TH150 TH200	8	14	380-415V 3N~ 220-240V 3~ 220-240V 1N~	310	310	1300	5 x 2.5/ 4 x 6.0/ 3 x 10	105	separat separate	3 x 20/ 3 x 32/ 1 x 40
TH6-80NB	8.0	3 x 1.5 3 x 1.15	TH150 TH115	7	14	380-415V 3N~ 220-240V 3~ 220-240V 1N~	355	355	1300	5 x 2.5/ 4 x 2.5/ 3 x 10	160	8 + 4h	3 x 16/ 3 x 20/ 1 x 40
TH6-90NB	9.0	6 x 1.5	TH150	8	15	380-415V 3N~ 220-240V 3~ 220-240V 1N~	355	355	1300	5 x 2.5/ 4 x 4.0/ 3 x 10	160	8 + 4h	3 x 16/ 3 x 25/ 1 x 40
TH6-80NS	8.0	3 x 1.5 3 x 1.15	TH150 TH115	7	14	380-415V 3N~ 220-240V 3~ 220-240V 1N~	355	355	1300	5 x 2.5/ 4 x 2.5/ 3 x 10	160	separat separate	3 x 16/ 3 x 20/ 1 x 40
TH6-90NS	9.0	6 x 1.5	TH150	8	15	380-415V 3N~ 220-240V 3~ 220-240V 1N~	355	355	1300	5 x 2.5/ 4 x 4.0/ 3 x 10	160	separat separate	3 x 16/ 3 x 25/ 1 x 40
										T1 T2 T1 & T2			T1 T2 T1 & T2
TH6-105N	10.5	2 x 2.0 3 x 1.5	TH200 TH150	9	16	380-415V 3N~	355	355	1300	5 x 1.5 5 x 1.5 5 x 2.5	160	separat separate	3 x 10 3 x 10 3 x 20
TH6-120N	12.0	6 x 2.0	TH200	11	18	380-415V 3N~	355	355	1300	5 x 1.5 5 x 1.5 5 x 4	160	separat separate	3 x 10 3 x 10 3 x 25
TH9-105N	10.5	9 x 1.15	TH115	10	16	380-415V 3N~	440	440	1300	5 x 1.5 5 x 1.5 3 x 2.5	230	separat separate	3 x 10 3 x 10 3 x 20
TH9-120N	12.0	4 x 1.15 5 x 1.5	TH115 TH150	11	20	380-415V 3N~	440	440	1300	5 x 1.5 5 x 1.5 5 x 4	230	separat separate	3 x 10 3 x 10 3 x 25
TH9-150N	15.0	6 x 1.5 3 x 2.0	TH150 TH200	14	25	380-415V 3N~	440	440	1300	5 x 2.5 5 x 1.5 5 x 4	230	separat separate	3 x 16 3 x 10 3 x 25
TH9-180N	18.0	9 x 2.0	TH200	18	28	380-415V 3N~	440	440	1300	5 x 1.5 5 x 2.5 -	230	separat separate	3 x 10 3 x 20 -
TH12-150N	15.0	9 x 1.15 3 x 1.5	TH115 TH150	15	26	380-415V 3N~	540	540	1300	5 x 2.5 5 x 1.5 5 x 4	360	separat separate	3 x 16 3 x 10 3 x 25
TH12-180N	18.0	12 x 1.5	TH150	18	30	380-415V 3N~	540	540	1300	5 x 1.5 5 x 2.5 -	360	separat separate	3 x 16 3 x 16 -
TH12-210N	21.0	6 x 1.5 6 x 2.0	TH150 TH200	22	35	380-415V 3N~	540	540	1300	5 x 2.5 5 x 2.5 -	360	separat separate	3 x 16 3 x 20 -
TH12-240N	24.0	12 x 2.0	TH200	24	40	380-415V 3N~	540	540	1300	5 x 2.5 5 x 2.5 -	360	separat separate	3 x 20 3 x 20 -